

# BITO PharmaBOX, with hinged two-part lid

## MBD43321HP | Data sheet



Pos. Dimensions, tolerances as specified in DIN 16901

A	Outside length top	410 mm
B	Outside width top	300 mm
C	Height	340 mm
D	Base length outside	318 mm
E	Base width outside	240 mm

### Product features

Weight	7.03 kg
*Load capacity	25 kg
Volume	4 litres
ESD	No
Food safety	✓
Material	PP
Stock item	-
Pcs/pack	1
colour	dove blue
Ref. no.	77-51178

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

\* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

### Dimensions, tolerances as specified in DIN 16901

Outside length top	410 mm
Outside width top	300 mm
Height	340 mm
Dimensions W x H x D	205 x 140 x 120 mm
Height of stacking rim	80 mm

### Printed message

Screen printing area on short side	120 x 110 mm
Screen printing area on short side (rear)	120 x 110 mm
Screen printing area on long side	200 x 100 mm
Hot foil printing area on short side (front)	150 x 100 mm
Hot foil printing area on short side (rear)	150 x 100 mm
Hot foil printing area on long side	240 x 100 mm
Injection mold printing area on long side	110 x 50 mm


Information & Service  
[www.bitocom](http://www.bitocom)

**BITO**  
 STORAGE  
 SYSTEMS

# BITO PharmaBOX, with hinged two-part lid MBD43321HP | Accessories



**Cold pack PCM 4°C - 700 ml**  
set of 4 pcs  
L 210 x W 135 x H 30 mm  
**77-51181**




**Syringe tray set**  
suited for BITO PharmaBOX  
containers  
L 206 x W 190 x H 166 mm  
**6-51228**



**TempBeacon data logger**  
L 88 x W 45 x H 16 mm  
**77-51235**



**Pt100 4-wire dry ice sensor**  
**77-51272**



**Pt100 4-wire liquid nitrogen sensor (LN2)**  
**77-51273**



**USB Type C charging cable**  
straight version  
L 1800 mm  
**77-51277**



**USB Power adapter**  
12 W  
**77-51278**