

Pos. Dimensions, Tolerances as specified in DIN 16901

A	Outside length top	500 mm
B	Outside width top	313 mm
C	Height	145 mm
F	Width of view and pick opening	242 mm
G	Height of view and pick opening	55 mm

Features	*Load capacity as specified in EN 13117
Proper weight	1.15 kg
*Stacking load	180 kg
*Load capacity	30 kg
Volume	17 Litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +90°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pallet	84
Pcs/pack	8
Colour	yellow
Ref. no.	2-1462

Other colours / special colours on request

Dimensions, Tolerances as specified in DIN 16901	
Outside length top	500 mm
Outside width top	313 mm
Height	145 mm
Inside length top	447 mm
Inside width top	281 mm
Inside length base	445 mm
Inside width base	278 mm
Inside height	132 mm
Stacking height	138 mm
Height below handle	30 mm
Pick opening W x H	242 x 55 mm
Label dimensions L x W	117 x 40 mm

Printed message	
Pad printing area on short side (front)	130 x 20 mm
Pad printing area on short side (rear)	250 x 80 mm
Pad printing area on long side	250 x 30 mm
Screen printing area on short side (rear)	220 x 50 mm
Hot foil printing area on short side (rear)	250 x 80 mm
Hot foil printing area on long side	250 x 30 mm
Injection mold printing area on long side	285 x 40 mm

Information & Service
www.bito.com

BITO
 STORAGE
 SYSTEMS

Storage bins SK

SK5031 | Accessories



Label covers
for storage bins SK
L 178 x W 42 mm
2-1066




Dust covers
for storage bins SK
L 482 x W 299 x H 2.5 mm
2-1136



Windows
for storage bins SK
2-11969



Handles
for storage bins SK
L 281 mm
2-19527



Labels
Printable label sheets
W 178 x H 40 mm
46-20776

Information & Service
www.bito.com

BITO
S T O R A G E
S Y S T E M S