
European size stacking containers XL, standard version

XL86221 | Data sheet





Product features	
Weight	4.52 kg
*Stacking load	800 kg
*Load capacity	60 kg
Volume	86 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	1
Material	PP
Stock item	✓
Pcs/pack	1
colour	blue
Ref. no.	43-22594

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901		
Outside length top	800 mm	
Outside width top	600 mm	
Height	220 mm	
Inside length top	762 mm	
Inside width top	562 mm	
Inside height	215 mm	
Printed message		
Pad printing area on short side (front)	40 x 180 mm	
Pad printing area on short side (rear)	40 x 180 mm	
Pad printing area on long side	70 x 180 mm	
Hot foil printing area on short side (front)	40 x 180 mm	
Hot foil printing area on short side (rear)	40 x 180 mm	
Hot foil printing area on long side	70 x 180 mm	
Injection mold printing area on long side	25 x 100 mm	

Information & Service www.bito.com



European size stacking containers XL, standard version

XL86221 | Accessories



Transport dollies for containers sized 800 x 600 mm L 800 x W 600 x H 198 mm **43-1150**



Covers for palletised loads L 1220 x W 820 mm 9-18421



Security sealsMBP2 - suited for BITOBOX MB **6-15705**



Security seals MBP2-L - suited for BITOBOX MB, XL, SL **6-19162**



Drop-on lid L 800 x W 600 mm **52-30500**



Barcoded security sealsMBP3 - suited for BITOBOX MBs in all sizes and XLs 800 x 600 mm **6-31550**



