
#### Small parts containers KLT with ribbed base, with hinged two-part lid

# KLTD64170R | Data sheet





Product features		
Weight	3.58 kg	
*Stacking load	500 kg	
*Load capacity	50 kg	
Volume	26 litres	
Warranty	5 year BITO QUALITY	
ESD	ESD version upon request	
Temperature range	-20°C to +80°C	
Food safety	✓	
Material	PP	
Stock item	✓	
Pcs/pack	1	
colour	turquoise	
Ref. no.	9-16808	

## Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

of 23 °C.

billions, tolerances as specifica in bill 10501		
Outside length top	600 mm	
Outside width top	400 mm	
Height	188 mm	
Inside length top	541 mm	

368 mm

150 mm

Dimensions, tolerances as specified in DIN 16901

Inside width top

Inside height

\* Load capacity data according to EN 13117 refer to an ambient temperature

Information & Service www.bito.com



### Small parts containers KLT with ribbed base, with hinged two-part lid

## KLTD64170R | Accessories



Labels


suited for BITOBOX XL and KLT with a height of at least 170 mm W 210 x H 74 mm

43-14557



**Security seals** 

for European size stacking containers XL and small parts containers KLT 9-16271



Slot-in divider strips

Material thickness 5 mm L 1150 x H 50 mm 43-18417



**Covers for palletised loads** 

L 1220 x W 820 mm

9-18421



#### **Label covers**

for European size stacking containers XL and small parts containers KLT W 209 x H 67 mm

9-20053



#### **Label covers**

for small parts containers KLT for European size stacking containers XL firm fit

W 218 x H 80 mm

9-20054



**Transport dollies** 

rubber wheels L 620 x W 420 mm

43-21883



3 sides open

6-5031



L 175 x W 105 mm





