
## Small parts containers KLT with ribbed base, with hinged two-part lid

# KLTD64220R | Data sheet





Product features	
Weight	3.91 kg
*Stacking load	500 kg
*Load capacity	50 kg
Volume	36 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	turquoise
Ref. no.	9-16276

Outside length top	600 mm
Outside width top	400 mm
Height	238 mm
Inside length top	541 mm

368 mm 200 mm

Dimensions, tolerances as specified in DIN 16901

Inside width top

Inside height

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

\* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Information & Service www.bito.com



## Small parts containers KLT with ribbed base, with hinged two-part lid

# KLTD64220R | Accessories



Labels

suited for BITOBOX XL and KLT with a height of at least 170 mm W 210 x H 74 mm

43-14557



**Security seals** 

for European size stacking containers XL and small parts containers KLT 9-16271



Slot-in divider strips

Material thickness 5 mm L 1150 x H 50 mm 43-18417



**Covers for palletised loads** 

L 1220 x W 820 mm

9-18421



### **Label covers**

for European size stacking containers XL and small parts containers KLT W 209 x H 67 mm

9-20053



#### **Label covers**

for small parts containers KLT for European size stacking containers XL firm fit

W 218 x H 80 mm

9-20054



### **Transport dollies**

rubber wheels L 620 x W 420 mm

43-21883



L 175 x W 105 mm



6-5031



Information & Service www.bito.com

