
Small parts containers KLT, with hinged two-part lid

KLTD64320 | Data sheet





Product features	
Weight	3.72 kg
*Stacking load	500 kg
*Load capacity	50 kg
Volume	58 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	turquoise
Ref. no.	9-16815

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901			
Outside length top	600 mm		
Outside width top	400 mm		
Height	338 mm		
Inside length top	541 mm		
Inside width top	368 mm		

316 mm

Inside height

Information & Service www.bito.com



Small parts containers KLT, with hinged two-part lid

KLTD64320 | Accessories



Labels

suited for BITOBOX XL and KLT with a height of at least 170 mm W 210 x H 74 mm

43-14557



Security seals

for European size stacking containers XL and small parts containers KLT 9-16271



Slot-in divider strips

Material thickness 5 mm L 1150 x H 50 mm 43-18417



Covers for palletised loads

L 1220 x W 820 mm

9-18421



Label covers

for European size stacking containers XL and small parts containers KLT W 209 x H 67 mm

9-20053



Label covers

for small parts containers KLT for European size stacking containers XL firm fit

W 218 x H 80 mm

9-20054



Transport dollies

rubber wheels L 620 x W 420 mm

43-21883



6-5031







