
Small parts containers KLT with ribbed base, with hinged two-part lid

KLTD64320R | Data sheet





Product features	
Weight	4.15 kg
*Stacking load	500 kg
*Load capacity	50 kg
Volume	55 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	turquoise
Ref. no.	9-16816
colour	

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions	tolerances a	as specified in	DIN 16901
, בווווכווטוטווט	tolclunces	is specifica iii	וטכטו וווע

Outside length top	600 mm
Outside width top	400 mm
Height	338 mm
Inside length top	541 mm
Inside width top	368 mm
Inside height	300 mm

Information & Service www.bito.com



Small parts containers KLT with ribbed base, with hinged two-part lid

KLTD64320R | Accessories



Labels


suited for BITOBOX XL and KLT with a height of at least 170 mm W 210 x H 74 mm

43-14557



Security seals

for European size stacking containers XL and small parts containers KLT 9-16271



Slot-in divider strips


Material thickness 5 mm L 1150 x H 50 mm 43-18417



Covers for palletised loads

L 1220 x W 820 mm

9-18421



Label covers

for European size stacking containers XL and small parts containers KLT W 209 x H 67 mm

9-20053



Label covers

for small parts containers KLT for European size stacking containers XL firm fit

W 218 x H 80 mm

9-20054



Transport dollies

rubber wheels L 620 x W 420 mm

43-21883

3 sides open

L 175 x W 105 mm



6-5031





