
European size stacking containers XL, with hinged two-part lid

XLD43271 | Data sheet





Product features	
Weight	1.88 kg
*Stacking load	250 kg
*Load capacity	30 kg
Volume	25 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	red
Ref. no.	43-14516

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

Dimensions, tolerances as specified in DIN 16901			
Outside length top	400 mm		
Outside width top	300 mm		
Height	288 mm		
Inside length top	368 mm		
Inside width top	268 mm		
Inside length base	359 mm		
Inside width base	259 mm		
Inside height	267 mm		
Printed message			
Pad printing area on short side (front)	90 x 180 mm		
Pad printing area on short side (rear)	90 x 180 mm		
Pad printing area on long side	90 x 230 mm		
Hot foil printing area on short side (front)	90 x 180 mm		
Hot foil printing area on short side (rear)	90 x 180 mm		
Hot foil printing area on long side	90 x 230 mm		
Injection mold printing area on long side	25 x 130 mm		

Information & Service www.bito.com



 $^{^{\}ast}$ Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

European size stacking containers XL, with hinged two-part lid

XLD43271 | Accessories



Security seals

for European size stacking containers XL and small parts containers KLT **9-16271**



Covers for palletised loads L 1220 x W 820 mm

9-18421



Drop-on lids

for European size stacking containers XL L 400 x W 300 mm

43-20303



Grip closures

for European size stacking containers XL with a height of 170, 220 and 270 mm **43-31450**



