










Kragarmregal Cantilever racking KR29

#12/2022/ Art.-Nr.: 14997




Aufbau- und Bedienanleitung (DE)
Instructions for assembly and use (GB)
Instructions de montage et d'utilisation (FR)
Richtlijnen en montagehandleiding (BE)
Instrucciones de montaje y manejo (ES)
Istruzioni per il montaggio e l'impiego (IT)
Montage- op betjeningsvejledning (DK)
összeállítási és kezelési útmutató (HU)
Instrukcja montażu i użytkowania (PL)
Návod k montáži a obsluze (CZ)
Návod na montáž a použitie (SK)
Інструкція по монтажу та експлуатації (UA)
Инструкция по сборке и использованию (RU)











DGUV 108-007






$H/350$



$H/350$






UBK1
 $t = 1 \text{ mm}$





C20/C25
DIN EN 206-1/DIN 1045-2






L	H
< 1 m	max. 4 mm
> 1 m - < 4 m	max. 10 mm
> 4 m - < 15 m	max. 12 mm
> 15 m	max. 15 mm




Mg [CO₃]












#	
1	6
2	7
3	8-9
4	10
5	10
6	11
7	12
8	12
9	13
10	14








1.














2.


















2		1x =		
				
3		M10x25 mm DIN EN ISO 4017	8.8	4x
4		Ø10,5 DIN EN ISO 708		4x
5		M10 DIN EN ISO 40	8	4x











	3				2x
	4		M12		2x
	5		M10x25 mm DIN EN ISO 4017	8.8	6x
	6		Ø10,5 DIN EN ISO 7089-		6x
	7		M10 DIN EN ISO 403	8	6x





1			▼	1x
2		M10x25 mm DIN 608	8.8	1x
3		M10 DIN EN ISO 403	8	1x
4		M10x25 mm DIN EN ISO 4017	8.8	1x
5		Ø10,5 DIN EN ISO 7089-		1x








IPE-100
IPE-120




IPE-140




2x











IPE-100
IPE-120



IPE-140








A

IPE-140	
H = 2500mm	L = 400mm
max. 4.800 kg	
29.378	
	$\frac{\text{kg}}{2}$
Installation	




$$= \frac{\text{kg}}{2}$$

B


Installation		mm	400	500	600	850
			kg/	kg/	kg/	kg/
1		NT	550	430	330	300
2		S	360	360	330	—
		max. 180 kg	max. 60 kg			




S/L



1






2






3

4






Qmax.					
I	H (mm)	NT (mm)			
		400	500	600	850
IPE-100	1.980	1.000 kg	850 kg	725 kg	-
IPE-120	2.480	1.400 kg	1.225 kg	1.075 kg	-
IPE-140	2.500	2.400 kg	2.050 kg	1.775 kg	1.350 kg
	3.220	2.225 kg	1.850 kg	1.600 kg	1.150 kg
	3.700	1.900 kg	1.600 kg	1.375 kg	1.000 kg






$$= \frac{\text{kg}}{2}$$




Qmax.					
I	H (mm)	NT (mm)			
		400	500	600	850
IPE-100	1.980	2.000 kg	1.700 kg	1.450 kg	-
IPE-120	2.480	2.800 kg	2.450 kg	2.150 kg	-
IPE-140	2.500	4.800 kg	4.100 kg	3.550 kg	2.700 kg
	3.220	4.450 kg	3.700 kg	3.200 kg	2.300 kg
	3.700	3.800 kg	3.200 kg	2.750 kg	2.000 kg





Q				
	NT (mm)			
	400	500	600	850
L	220 kg	175 kg	140 kg	-
S	550 kg	430 kg	330 kg	300 kg




Q				
	NT (mm)			
	400	500	600	850
L	220 kg	175 kg	140 kg	-
S	360 kg	360 kg	330 kg	-



Q			
NT (mm)			
400	500	600	850
460 kg	420 kg	370 kg	-




max. 180 kg



max. 60 kg

Kragarmregal Cantilever racking KR29

#12/2022/ Art.-Nr.: 14997



Kragarmregal/0,5/12-2022 | Technische Änderungen vorbehalten. Technical modifications reserved.

Wir freuen uns auf Ihr Feedback!
Looking forward to your feedback!

feedbackmontage@bito.com