

BITO PharmaBOX, with a two-piece hinged lid, including a recessed area to accommodate the SmartHub/SmartLock

MBDSH64321 | Data sheet



Pos. Dimensions, tolerances as specified in DIN 16901

A	Outside length top	610 mm
B	Outside width top	400 mm
C	Height	340 mm
D	Base length outside	505 mm
E	Base width outside	335 mm

Product features

Weight	11.76 kg
*Stacking load	200 kg
*Load capacity	35 kg
Volume	15 litres
ESD	No
Food safety	✓
Material	PP
Stock item	–
Pcs/pack	1
colour	dove blue
Ref. no.	77-51173

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901

Outside length top	610 mm
Outside width top	400 mm
Height	340 mm
Dimensions W x H x D	420 x 215 x 135 mm
Height of stacking rim	80 mm

Printed message

Screen printing area on short side	120 x 110 mm
Screen printing area on short side (rear)	120 x 110 mm
Screen printing area on long side	200 x 100 mm
Hot foil printing area on short side (front)	240 x 100 mm
Hot foil printing area on short side (rear)	240 x 100 mm
Hot foil printing area on long side	250 x 100 mm
Injection mold printing area on long side	235 x 50 mm

Information & Service
www.bito.com

BITO
STORAGE
SYSTEMS

BITO PharmaBOX, with a two-piece hinged lid, including a recessed area to accommodate the SmartHub/SmartLock

MBDSH64321 | Accessories



Cold pack PCM 4°C – 700 ml
set of 4 pcs
L 210 x W 135 x H 30 mm
77-51181



TempBeacon data logger
L 88 x W 45 x H 16 mm
77-51235



SmartLock
Gateway monitoring system
L 129 x W 129 x H 35 mm
77-51268




SmartHub
Gateway monitoring system
L 129 x W 129 x H 29 mm
77-51269



SmartHub Alkaline
Gateway monitoring system
L 129 x W 129 x H 29 mm
77-51270



Pt100 4-wire dry ice sensor
77-51272



Pt100 4-wire liquid nitrogen sensor (LN2)
77-51273




USB Type C charging cable
straight version
L 1800 mm
77-51277



USB Power adapter
12 W
77-51278



Data tariff worldwide SmartHub/SmartLock
77-51360



Data tariff Europe-wide SmartHub/SmartLock
77-51361