
Storage and handling bins RK Eco

RK4109Eco | Data sheet





Product features		
Weight	0.32 kg	
*Stacking load	9 kg	
*Load capacity	3 kg	
Volume	2.7 litres	
Warranty	2 year warranty	
ESD	ESD version upon request	
Temperature range	-20°C to +80°C	
Food safety	-	
Material	recycled polypropylene	
Stock item	✓	
Pcs/pack	16	
colour	black	
Ref. no.	C0220-0032	

Dimensions, tolerances as specified in DIN 16901				
Outside length top	400 mm			
Outside width top	117 mm			
Height	90 mm			
Inside length top	360 mm			
Inside width top	94 mm			
Inside length base	358 mm			
Inside width base	92 mm			
Inside height	80 mm			
Dimensions W x H x D	mm			

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Information & Service www.bito.com




Storage and handling bins RK Eco

RK4109Eco | Accessories



Label coversfor storage and handling bins RK
L 84 x W 40 mm **3-1062**




Dust coversfor storage and handling bins RK L 365 x W 106 mm **3-1128**



Carry/safety handle for storage and handling bins RK **3-1514**



Cross dividers for storage and handling bins RK **3-1588**



Label sheets W 84 x H 39 mm **46-20768**

Information & Service www.bito.com

