
European size stacking containers XL, with perforated base and perforated sides **XL43223** | Data sheet





Product features

Floduct leatures	
Weight	1.13 kg
*Stacking load	250 kg
*Load capacity	35 kg
Volume	18 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	1
Material	РР
Stock item	\checkmark
Pcs/pack	1
colour	blue
Ref. no.	43-18521

Dimensions, tolerances as specified in DIN 16901

Outside length top	400 mm
Outside width top	300 mm
Height	220 mm
Inside length top	368 mm
Inside width top	268 mm
Inside length base	359 mm
Inside width base	259 mm
Inside height	202 mm
Printed message	

Injection mold printing area on long side

25 x 130 mm

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Information & Service
www.bito.com



European size stacking containers XL, with perforated base and perforated sides **XL43223** | Accessories



Covers for palletised loads L 1220 x W 820 mm 9-18421



Drop-on lids for European size stacking containers XL L 400 x W 300 mm 43-20303



Grip closures

for European size stacking containers XL with a height of 170, 220 and 270 mm **43-31450**

Information & Service **www.bito.com**

