


Small parts containers KLT, hinged on one side and closed with 2 snap locks on the other side

KLT43220ASDV | Data sheet



Pos. Dimensions, tolerances as specified in DIN 16901

Pos.	Dimensions, tolerances as specified in DIN 16901	
A	Outside length top	400 mm
B	Outside width top	300 mm
C	Height	238 mm

Product features	*Load capacity as specified in EN 13117
Weight	1.85 kg
*Stacking load	300 kg
*Load capacity	50 kg
Volume	17.80 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	turquoise
Ref. no.	9-22250

Other colours / special colours on request

Dimensions, tolerances as specified in DIN 16901	
Outside length top	400 mm
Outside width top	300 mm
Height	238 mm
Inside length top	341 mm
Inside width top	268 mm
Inside height	216 mm

Information & Service
www.bito.com

BITO
STORAGE
SYSTEMS

Small parts containers KLT, hinged on one side and closed with 2 snap locks on the other side


KLT43220ASDV | Accessories



Labels

suited for BITOBOX XL and KLT with a height of at least 170 mm
W 210 x H 74 mm

43-14557



Slot-in divider strips

Material thickness 5 mm
L 1150 x H 50 mm


43-18417



Covers for palletised loads

L 1220 x W 820 mm

9-18421



Label covers

for European size stacking containers
XL and small parts containers KLT
W 209 x H 67 mm

9-20053



Transport dollies

rubber wheels
L 620 x W 420 mm

43-21883



Document pockets

self-adhesive
3 sides open
L 175 x W 105 mm

6-5031