

Storage and handling bins RK RK4108 | Data sheet



Pos. Dimensions, tolerances as specified in DIN 16901

A	Outside length top	400 mm
B	Outside width top	117 mm
C	Height	80 mm

Product features

Weight	0.30 kg
*Stacking load	9 kg
*Load capacity	3 kg
Volume	2.5 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	-
Material	recycled polypropylene
Stock item	✓
Pcs/pack	16
colour	dove blue
Ref. no.	3-19146

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901


Outside length top	400 mm
Outside width top	117 mm
Height	80 mm
Inside length top	360 mm
Inside width top	95 mm
Inside length base	358 mm
Inside width base	93 mm
Inside height	70 mm
Dimensions W x H x D	mm

Information & Service
www.bitto.com

BITO
STORAGE
SYSTEMS

Storage and handling bins RK


RK4108 | Accessories



Dust covers
for storage and handling bins RK
L 365 x W 106 mm
3-1128




Carry/safety handle
for storage and handling bins RK
3-1514



Label covers
for storage and handling bins RK
L 89 x W 30 mm
3-19140



Cross dividers
for storage and handling bins RK
3-19148



Label sheets
W 89 x H 30 mm
46-20767

Information & Service
www.bito.com

BITO
STORAGE
SYSTEMS