

Storage and handling bins RK

RK6109 | Data sheet





	Weight	0.51 kg
	*Stacking load	15 kg
	*Load capacity	5 kg
	Volume	4.0 litres
	Warranty	5 year BITO QUALITY
	ESD	ESD version upon request
	Temperature range	-20°C to +80°C
	Food safety	-
	Material	recycled polypropylene
	Stock item	✓
	Pcs/pack	16
	colour	dove blue
	Ref. no.	3-1442

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimoncione	tolerances a	c cnacifiad	in	DIN 16001


Outside length top	600 mm	
Outside width top	117 mm	
Height	90 mm	
Inside length top	560 mm	
Inside width top	94 mm	
Inside length base	555 mm	
Inside width base	92 mm	
Inside height	80 mm	
Dimensions W x H x D	mm	

Information & Service www.bito.com




Storage and handling bins RK

RK6109 | Accessories



Label coversfor storage and handling bins RK
L 84 x W 40 mm **3-1062**




Dust covers for storage and handling bins RK L 564 x W 106 mm **3-1132**



Carry/safety handle for storage and handling bins RK **3-1514**



Cross dividers for storage and handling bins RK **3-1588**



Label sheets W 84 x H 39 mm **46-20768**

Information & Service www.bito.com

