
SK1610Eco | Data sheet





Product features		
Weight	0.09 kg	
*Load capacity	2 kg	
Volume	0.8 litres	
Warranty	2 year warranty	
ESD	ESD version upon request	
Temperature range	-20°C to +80°C	
Food safety	-	
Material	recycled polypropylene	
Stock item	-	
Pcs/pallet	1000	
Pcs/pack	40	
colour	black	
Ref. no.	C0230-0131	

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901			
Outside length top	160 mm		
Outside width top	103 mm		
Height	75 mm		
Inside length top	139 mm		
Inside width top	87 mm		
Inside length base	136 mm		
Inside width base	85 mm		
Inside height	68 mm		
Stacking height	68 mm		
Height below handle	13 mm		
Pick opening W x H	78 x 31 mm		
Label dimensions L x W	70 x 20 mm		
Printed message			
Pad printing area on short side (front)	40 x 10 mm		
Pad printing area on short side (rear)	60 x 30 mm		
Pad printing area on long side	110 x 40 mm		
Injection mold printing area on long side	110 x 25 mm		

Information & Service www.bito.com



Storage bins SK Eco

SK1610Eco | Accessories




Label covers for storage bins SK L 71 x W 21 mm **2-1061**




Insertable windows for storage bins SK **2-1108**




Drop-on lids for storage bins SK L 149 x W 98/77 mm **2-19870**



Label sheets W 70.5 x H 20 mm **46-20774**



Louvred panel uprights L 1000 x W 35 x H 25 mm **8-5928**



Bin suspension rails L 1126 mm **8-7869**

Information & Service www.bito.com

