
# Small parts containers KLT, with hinged two-part lid **KLTD64270** | Data sheet





### Product features

Weight	3.65 kg
*Stacking load	500 kg
*Load capacity	50 kg
Volume	48 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	1
Material	РР
Stock item	✓
Pcs/pack	1
colour	turquoise
Ref. no.	9-16811

#### Dimensions, tolerances as specified in DIN 16901

Outside length top	600 mm
Outside width top	400 mm
Height	288 mm
Inside length top	541 mm
Inside width top	368 mm
Inside height	266 mm

## Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 $^{\ast}$  Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Information & Service
www.bito.com



## Small parts containers KLT, with hinged two-part lid **KLTD64270** | Accessories




suited for BITOBOX XL and KLT with a height of at least 170 mm W 210 x H 74 mm **43-14557** 



Security seals for European size stacking containers XL and small parts containers KLT 9-16271



Covers for palletised loads L 1220 x W 820 mm 9-18421



Slot-in divider strips Material thickness 5 mm L 1150 x H 50 mm 43-18417



Label covers for European size stacking containers XL and small parts containers KLT W 209 x H 67 mm 9-20053



Label covers

for small parts containers KLT for European size stacking containers XL firm fit W 218 x H 80 mm **9-20054** 



**Transport dollies** rubber wheels L 620 x W 420 mm **43-21883** 



**Document pockets** self-adhesive 3 sides open L 175 x W 105 mm **6-5031** 

Information & Service **www.bito.com** 

