

Storage and handling bins RK RK5214 | Data sheet



Pos. Dimensions, tolerances as specified in DIN 16901

Pos.	Dimensions, tolerances as specified in DIN 16901	
A	Outside length top	500 mm
B	Outside width top	234 mm
C	Height	140 mm

Product features

Weight	0.86 kg
*Stacking load	40 kg
*Load capacity	13 kg
Volume	12.0 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	-
Pcs/pack	6
colour	dove blue
Ref. no.	3-1441

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901


Outside length top	500 mm
Outside width top	234 mm
Height	140 mm
Inside length top	453 mm
Inside width top	210 mm
Inside length base	452 mm
Inside width base	208 mm
Inside height	129 mm

Information & Service
www.bito.com


BITO
STORAGE
SYSTEMS

Storage and handling bins RK


RK5214 | Accessories



Label covers
for storage and handling bins RK
L 192 x W 60 mm
3-1068



Longitudinal dividers
for storage and handling bins RK
3-1082



Dust covers
for storage and handling bins RK
L 462 x W 223 mm
3-1131



Carry/safety handle
for storage and handling bins RK
3-1515



Cross dividers
for storage and handling bins RK
3-1591



Label sheets
W 192 x H 60 mm
46-20772