
European size stacking containers XL, with hinged two-part lid

XLD43221 | Data sheet





Product features	
Weight	1.69 kg
*Stacking load	250 kg
*Load capacity	30 kg
Volume	20 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	blue
Ref. no.	43-18523

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901		
Outside length top	400 mm	
Outside width top	300 mm	
Height	238 mm	
Inside length top	368 mm	
Inside width top	268 mm	
Inside length base	359 mm	
Inside width base	259 mm	
Inside height	217 mm	
Printed message		
Pad printing area on short side (front)	40 x 180 mm	
Pad printing area on short side (rear)	40 x 180 mm	
Pad printing area on long side	40 x 230 mm	
Hot foil printing area on short side (front)	40 x 180 mm	
Hot foil printing area on short side (rear)	40 x 180 mm	
Hot foil printing area on long side	40 x 230 mm	
Injection mold printing area on long side	25 x 130 mm	

Information & Service www.bito.com



European size stacking containers XL, with hinged two-part lid

XLD43221 | Accessories



Security seals

for European size stacking containers XL and small parts containers KLT **9-16271**



Covers for palletised loads L 1220 x W 820 mm

9-18421



Drop-on lids

for European size stacking containers XL L 400 x W 300 mm

43-20303



Grip closures

for European size stacking containers XL with a height of 170, 220 and 270 mm **43-31450**



