
European size stacking containers XL, hinged on one side and closed with 2 snap locks on the other side

XL64421ASDV | Data sheet





Product features	
Weight	4.07 kg
*Stacking load	300 kg
*Load capacity	20 kg
Volume	82 litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +80°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
colour	blue
Ref. no.	43-22257

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

Dimensions, tolerances as specified in DIN 16901			
Outside length top	600 mm		
Outside width top	400 mm		
Height	438 mm		
Inside length top	568 mm		
Inside width top	368 mm		
Inside length base	559 mm		
Inside width base	359 mm		
Inside height	416 mm		
Printed message			
Pad printing area on short side (front)	100 x 250 mm		
Pad printing area on short side (rear)	100 x 250 mm		
Pad printing area on long side	100 x 250 mm		
Hot foil printing area on short side (front)	100 x 250 mm		
Hot foil printing area on short side (rear)	100 x 250 mm		
Hot foil printing area on long side	100 x 250 mm		
Injection mold printing area on long side	25 x 100 mm		

Information & Service www.bito.com



^{*} Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

European size stacking containers XL, hinged on one side and closed with 2 snap locks on the other side

XL64421ASDV | Accessories



Covers for palletised loads L 1220 x W 820 mm 9-18421



Transport dollies rubber wheels L 620 x W 420 mm **43-21883**



Grip closures for European size stacking containers XL with a height of 320 and 420 mm **43–31448**

Information & Service www.bito.com

