
### European size stacking containers XL with double base

## XL64271D | Data sheet





Product features		
Weight	2.67 kg	
*Stacking load	300 kg	
*Load capacity	100 kg	
Volume	50 litres	
Warranty	5 year BITO QUALITY	
ESD	No	
Temperature range	-20°C to +60°C	
Food safety	-	
Material	PP	
Stock item	✓	
Pcs/pack	1	
colour	bins in blue - base in black	
Ref. no.	43-19032	

#### Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

\* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C

Dimensions, tolerances as specified in DIN 16901			
Outside length top	600 mm		
Outside width top	400 mm		
Height	270 mm		
Inside length top	568 mm		
Inside width top	368 mm		
Inside length base	559 mm		
Inside width base	359 mm		
Inside height	252 mm		
Printed message			
Pad printing area on short side (front)	90 x 250 mm		
Pad printing area on short side (rear)	90 x 250 mm		
Pad printing area on long side	90 x 250 mm		
Hot foil printing area on short side (front)	90 x 250 mm		
Hot foil printing area on short side (rear)	00 v 250 mm		
riot fon printing area on short side (rear)	90 x 250 mm		
Hot foil printing area on long side	90 x 250 mm		

Information & Service www.bito.com



### European size stacking containers XL with double base

# XL64271D | Accessories



Covers for palletised loads L 1220 x W 820 mm 9-18421



**Drop-on lids**for European size stacking containers XL L 600 x W 400 mm
43-20301



**Transport dollies** rubber wheels L 620 x W 420 mm **43-21883** 



**Grip closures** for European size stacking containers XL with a height of 170, 220 and 270 mm **43–31450** 



