


Small parts containers KLT with ribbed base

KLT43270R | Data sheet



Pos. Dimensions, Tolerances as specified in DIN 16901

A	Outside length top	400 mm
B	Outside width top	300 mm
C	Height	270 mm

Features	*Load capacity as specified in EN 13117
Proper weight	1.69 kg
*Stacking load	300 kg
*Load capacity	50 kg
Volume	20 Litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +90°C
Food safety	✓
Material	PP
Stock item	-
Pcs/pack	1
Colour	turquoise
Ref. no.	9-16802

Dimensions, Tolerances as specified in DIN 16901	
Outside length top	400 mm
Outside width top	300 mm
Height	270 mm
Inside length top	341 mm
Inside width top	268 mm
Inside height	250 mm

Other colours / special colours on request

Information & Service
www.bitocom

BITO
 STORAGE
 SYSTEMS

Small parts containers KLT with ribbed base KLT43270R | Accessories




Locking systems BS
for small parts containers KLT
7-14434




Labels
W 210 x H 74 mm
43-14557




Transport dolly
polypropylene wheels
L 620 x W 420 mm
43-1491




Slot-in divider strips
Material thickness 5 mm
L 1150 x H 180 mm
7-15509



Slot-in divider strips
Material thickness 5 mm
L 1150 x H 50 mm
43-18417



Slot-in divider strips
Material thickness 5 mm
L 1150 x H 80 mm
43-18418



Slot-in divider strips
Material thickness 10 mm
L 950 x H 55 mm
43-18419



Slot-in divider strips
Material thickness 10 mm
L 950 x H 120 mm
43-18420




Covers for palletised containers
L 1220 x W 820 mm
9-18421



Label covers
for European size stacking containers
XL and small parts containers KLT
W 209 x H 67 mm
9-20053



Label covers
for small parts containers KLT
firm fit
W 218 x H 80 mm
9-20054



Drop-on lids
for small parts containers KLT
L 400 x W 300 mm
43-20499



Drop-on lids
hinge-clipped on one side
KLT container with hinged lid
L 400 x W 300 mm
43-21520



Transport dolly
rubber wheels
L 620 x W 420 mm
43-21883



Document pockets
self-adhesive
3 sides open
L 175 x W 105 mm
6-5031