


Small parts containers KLT

KLT64170 | Data sheet

Pos.	Dimensions, Tolerances as specified in DIN 16901	
A	Outside length top	600 mm
B	Outside width top	400 mm
C	Height	170 mm

Features	*Load capacity as specified in EN 13117
Proper weight	2.05 kg
*Stacking load	500 kg
*Load capacity	30 kg
Volume	29 Litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +90°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pack	1
Colour	turquoise
Ref. no.	9-16805

Dimensions, Tolerances as specified in DIN 16901	
Outside length top	600 mm
Outside width top	400 mm
Height	170 mm
Inside length top	541 mm
Inside width top	368 mm
Inside height	166 mm

Other colours / special colours on request

Information & Service
www.bitto.com

BITO
 STORAGE
 SYSTEMS

Small parts containers KLT

KLT64170 | Accessories




Locking systems BS
for small parts containers KLT
7-14434




Labels
W 210 x H 74 mm
43-14557




Transport dolly
polypropylene wheels
L 620 x W 420 mm
43-1491




Slot-in divider strips
Material thickness 5 mm
L 1150 x H 180 mm
7-15509




Slot-in divider strips
Material thickness 5 mm
L 1150 x H 50 mm
43-18417



Slot-in divider strips
Material thickness 5 mm
L 1150 x H 80 mm
43-18418



Slot-in divider strips
Material thickness 10 mm
L 950 x H 55 mm
43-18419



Slot-in divider strips
Material thickness 10 mm
L 950 x H 120 mm
43-18420




Covers for palletised containers
L 1220 x W 820 mm
9-18421



Label covers
for European size stacking containers
XL and small parts containers KLT
W 209 x H 67 mm
9-20053



Label covers
for small parts containers KLT
firm fit
W 218 x H 80 mm
9-20054



Drop-on lids
for small parts containers KLT
L 600 x W 400 mm
43-20497



Drop-on lids
hinge-clipped on one side
KLT container with hinged lid
L 600 x W 400 mm
43-21523



Transport dolly
rubber wheels
L 620 x W 420 mm
43-21883



Document pockets
self-adhesive
3 sides open
L 175 x W 105 mm
6-5031