
Storage and handling bins RK

RK3209 | Data sheet





	Product features	
	Weight	0.39 kg
	*Stacking load	15 kg
	*Load capacity	5 kg
	Volume	4.4 litres
	Warranty	5 year BITO QUALITY
	ESD	ESD version upon request
	Temperature range	-20°C to +80°C
	Food safety	-
	Material	recycled polypropylene
	Stock item	✓
	Pcs/pack	8
	colour	dove blue
	Ref. no.	3-1434

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

 * Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions	talarancas	oc concified	in	DIM 16001
	10161411167	47 7000000	- 11 1	THIN INSUL


Outside length top	300 mm	
Outside width top	234 mm	
Height	90 mm	
Inside length top	256 mm	
Inside width top	211 mm	
Inside length base	254 mm	
Inside width base	208 mm	
Inside height	80 mm	
Dimensions W x H x D	mm	

Information & Service www.bito.com




Storage and handling bins RK


RK3209 | Accessories



Label covers for storage and handling bins RK L 192 x W 40 mm **3-1067**



Longitudinal dividers for storage and handling bins RK **3-1077**




Dust coversfor storage and handling bins RK
L 263 x W 222 mm **3-1127**



Carry/safety handle for storage and handling bins RK **3-1515**



Cross dividers for storage and handling bins RK **3-1590**



Label sheets W 192 x H 39 mm **46-20771**



