

Pos. Dimensions, Tolerances as specified in DIN 16901

A	Outside length top	500 mm
B	Outside width top	313 mm
C	Height	300 mm
F	Width of view and pick opening	241 mm
G	Height of view and pick opening	133 mm

Features	*Load capacity as specified in EN 13117
Proper weight	1.96 kg
*Stacking load	150 kg
*Load capacity	35 kg
Volume	36 Litres
Warranty	5 year BITO QUALITY
ESD	ESD version upon request
Temperature range	-20°C to +90°C
Food safety	✓
Material	PP
Stock item	✓
Pcs/pallet	36
Pcs/pack	4
Colour	red
Ref. no.	2-14893

Other colours / special colours on request

Dimensions, Tolerances as specified in DIN 16901	
Outside length top	500 mm
Outside width top	313 mm
Height	300 mm
Inside length top	448 mm
Inside width top	282 mm
Inside length base	445 mm
Inside width base	278 mm
Inside height	286 mm
Stacking height	293 mm
Height below handle	88 mm
Pick opening W x H	241 x 133 mm
Label dimensions L x W	178 x 56 mm

Printed message	
Pad printing area on short side (front)	250 x 50 mm
Pad printing area on short side (rear)	250 x 100 mm
Pad printing area on long side	250 x 100 mm
Screen printing area on short side (rear)	220 x 200 mm
Hot foil printing area on short side (rear)	250 x 100 mm
Hot foil printing area on long side	250 x 100 mm
Injection mold printing area on long side	290 x 55 mm

Information & Service
www.bito.com

BITO
 STORAGE
 SYSTEMS

Storage bins SK

SK5033 | Accessories



Longitudinal dividers
for storage bins SK
2-1075



Dust covers
for storage bins SK
L 482 x W 299 x H 2.5 mm
2-1136




Windows
for storage bins SK
2-14578



Label covers
for storage bins SK
L 178 x W 58 mm
2-14897



Handles
for storage bins SK
L 281 mm
2-19527



Labels
Printable label sheets
W 178 x H 56 mm
46-20777