

BITO PharmaBOX, with a two-piece hinged lid, including a recessed area to accommodate the SmartHub/SmartLock

MBDSH43321 | Data sheet



Pos.	Dimensions, tolerances as specified in DIN 16901	
A	Outside length top	410 mm
B	Outside width top	300 mm
C	Height	340 mm
D	Base length outside	318 mm
E	Base width outside	240 mm

Product features	
Weight	7.03 kg
*Load capacity	25 kg
Volume	4 litres
ESD	No
Food safety	✓
Material	PP
Stock item	–
Pcs/pack	1
colour	dove blue
Ref. no.	77-51174

Other colours / special colours on request

All written or verbal information about product properties and product application are given to the best of our knowledge. This information is based on our experience and cannot be warranted as the sole binding product properties. It is the customer's responsibility to check whether the ordered goods are suitable for the intended use. All measurements are subject to variations within the scope of the applicable manufacturing tolerances.

* Load capacity data according to EN 13117 refer to an ambient temperature of 23 °C.

Dimensions, tolerances as specified in DIN 16901	
Outside length top	410 mm
Outside width top	300 mm
Height	340 mm
Dimensions W x H x D	205 x 140 x 120 mm
Height of stacking rim	80 mm
Printed message	
Screen printing area on short side	120 x 110 mm
Screen printing area on short side (rear)	120 x 110 mm
Screen printing area on long side	200 x 100 mm
Hot foil printing area on short side (front)	150 x 100 mm
Hot foil printing area on short side (rear)	150 x 100 mm
Hot foil printing area on long side	240 x 100 mm
Injection mold printing area on long side	110 x 50 mm

Information & Service
www.bito.com



BITO PharmaBOX, with a two-piece hinged lid, including a recessed area to accommodate the SmartHub/SmartLock

MBDSH43321 | Accessories



Cold pack PCM 4°C – 700 ml
set of 4 pcs
L 210 x W 135 x H 30 mm
77-51181



TempBeacon data logger
L 88 x W 45 x H 16 mm
77-51235



SmartLock
Gateway monitoring system
L 129 x W 129 x H 35 mm
77-51268




SmartHub
Gateway monitoring system
L 129 x W 129 x H 29 mm
77-51269



SmartHub Alkaline
Gateway monitoring system
L 129 x W 129 x H 29 mm
77-51270



Pt100 4-wire dry ice sensor
77-51272



Pt100 4-wire liquid nitrogen sensor (LN2)
77-51273




USB Type C charging cable
straight version
L 1800 mm
77-51277



USB Power adapter
12 W
77-51278



Data tariff worldwide SmartHub/SmartLock
77-51360



Data tariff Europe-wide SmartHub/SmartLock
77-51361